



VFT


# Reduktion m/w

## Eigenschaften

- Geeignet für den Einsatz bis zu 4.150 bar/ 60.000 psi oder 6.200 bar/ 90.000 psi
- Verfügbar in metrisch oder imperial
- Sonderabmessungen auf Anfrage



## Technische Daten



Artikel Nummer	Max. Druck [bar/psi]	Außengewinde	Innengewinde	Maße [mm]				
				A	B	C	D	F
<b>1/4" - 3/8"</b>								
651438	4.150 / 60.000	M16 x 1,5	M20 x 1,5	28	27	22	13	17
651438-I	4.150 / 60.000	9/16" - 18UNF	3/4" - 16UNF	29	27	13/16"	12	17
651438-P	6.200 / 90.000	M16 x 1,5	M20 x 1,5	28	27	22	13	17
<b>1/4" - 9/16"</b>								
651491	4.150 / 60.000	M16 x 1,5	M30 x 2	31	41	32	16	17
651491-I	4.150 / 60.000	9/16" - 18UNF	1 1/8" - 12UNF	31	41	1 3/16"	18	17
651491-P	6.200 / 90.000	M16 x 1,5	M30 x 2	31	41	32	16	17
<b>3/8" - 1/4"</b>								
653814	4.150 / 60.000	M20 x 1,5	M16 x 1,5	19	22	17	13	21
653814-I	4.150 / 60.000	3/4" - 16UNF	9/16" - 18UNF	18	22	5/8"	13	21
653814-P	6.200 / 90.000	M20 x 1,5	M16 x 1,5	19	22	17	13	21
<b>3/8" - 9/16"</b>								
653891	4.150 / 60.000	M20 x 1,5	M30 x 2	31	41	32	15	21
653891-I	4.150 / 60.000	3/4" - 16UNF	1 1/8" - 12UNF	31	41	1 3/16"	18	21
653891-P	6.200 / 90.000	M20 x 1,5	M30 x 2	31	41	32	15	21
<b>9/16" - 1/4"</b>								
659114	4.150 / 60.000	M30 x 2	M16 x 1,5	16	32	17	13	30
659114-I	4.150 / 60.000	1 1/8" - 12UNF	9/16" - 18UNF	18,5	30	5/8"	13	27,5
659114-P	6.200 / 90.000	M30 x 2	M16 x 1,5	16	32	17	13	30
<b>9/16" - 3/8"</b>								
659138	4.150 / 60,000	M30 x 2	M20 x 1,5	24	32	22	13	30
659138-I	4.150 / 60,000	1 1/8" - 12UNF	3/4" - 16UNF	26,5	32	13/16"	12	27,5
659138-P	6.200 / 90,000	M30 x 2	M20 x 1,5	24	32	22	13	30

Weitere Informationen unter

ALLFI website : [allfi.com](http://allfi.com)  
 ALLFI webshop : [allfiwaterjetparts.com](http://allfiwaterjetparts.com)  
 Kontakt : [info@allfi.com](mailto:info@allfi.com)

Superior Waterjet Parts

